

# Additel 673

## Advanced Digital Pressure Calibrators

- Pressure ranges up to 60,000 psi (4,200 bar)
- 0.02%, 0.05% FS or 0.1% RD Accuracy
- Color Touchscreen Display
- Every model measures Gauge or Absolute Pressure
- Built-in Barometer
- Intuitive Smartphone Like Interface
- Bluetooth and USB Communication
- Wi-Fi (optional)
- Measure mA or V, and with 24V loop power
- Full HART Field Communicator (Optional)
- Data logging
- Communicates with Additel's Link Mobile App



Additel 673

### OVERVIEW

Additel's 673 Advanced Digital Pressure Calibrators will redefine the way you want to measure and calibrate pressure readings and devices! With wireless remote connectivity, microprocessor technology, state of-the-art silicon pressure sensors and onboard storage capacity, these attractive and fully temperature compensated calibrators will provide the performance, durability and reliability you've come to expect from genuine Additel products. The all new modern menu structure and control interface brings a new and refreshing experience to pressure calibration work. This completely new way of interfacing with our pressure calibrators makes the ADT673 a real pleasure to use. The handy Additel Link app gives users the ability to remotely monitor these calibrators from the convenience of a personal device or cell phone. With an abundance of options to choose from, you can configure these pressure calibrators to precisely fit your specific pressure calibration and measurement needs. With an IP67 rating, you will find that these amazing pressure calibrators can be used in the field or laboratory to meet the most demanding pressure calibration needs.

#### A Modern User Experience:

Additel has gone above and beyond to provide our customers with the best possible experience when using this new and revolutionary calibrator. The 3.4 inch color touchscreen display comes with a protective replaceable tempered glass screen and is a refreshing update to the traditional push button or blister pad interface. With an easy to navigate menu structure and fast touchscreen response, you will find these ADT673 calibrators simple yet powerful to use. The easy to read display isn't just fun to use, but it's built rugged to handle the demands of a busy technician in the field or the laboratory.



#### HART Field Communicator :

With full support for HART communication protocols, the ADT673 Advanced Digital Pressure Calibrators provide a pressure calibration solution for transmitters over a wide pressure range. The ADT673 is a very portable device and can measure pressure precisely with a built-in pressure sensor, as well as read the current or mV produced by a transducer. It can even supply an excitation voltage (loop power) to power sensors or transmitters during calibration.



## SPECIFICATIONS

Accuracy	673-02: 0.02% of full span
	673-05: 0.05% of full span
	673-RD: 0% to 20% of range: 0.02% of full span 20% to 110% of range: 0.1% of reading
	Vacuum: 0.25% of full span <sup>[1][2]</sup> Built-in barometer: 55 Pa
Gauge Types	Gauge pressure, compound pressure, absolute pressure, differential pressure Color Touchscreen (capacitive)
Display	Screen protector: tempered glass film (replaceable)
	Display rate: 3 readings per second (Default setting). Adjustable from 10 readings per second to 1 reading every 20 seconds
	Resolution: 4, 5 or 6 digits (user selectable)
Pressure Units <sup>[5]</sup>	Pa, kPa, MPa, psi, bar, mbar, kgf/cm <sup>2</sup> , inH <sub>2</sub> O@4°C mmH <sub>2</sub> O@4°C, inHg@0°C, mmHg@0°C and 5 customizable units
Environmental	Compensated Temp.: 14°F to 122°F (-10°C to 50°C)
	Operating Temp.: 14°F to 122°F (-10°C to 50°C)
	Storage Temp.: -4°F to 158°F (-20°C to 70°C)
	Humidity: 0 - 95%, Non-condensing
Pressure Port	≤ 15,000 psi: 1/4NPT male, 1/2NPT male, 1/4BSP male, 1/2BSP male, M20x1.5 male >15,000 psi: 1/4HP female or 1/4HP male *1/4HP female: Autoclave F-250-C, 9/16" - 18 UNF-2B *1/4HP male: Autoclave M-250-C, 9/16" - 18 UNF-2A
	Differential Pressure: barb fitting
	Other connections available per request
Over Pressure Warning	120%
Power	Battery: rechargeable Li-ion battery
	Li-Battery life: 16 hours typically
	Recharge time: 4 hours typically
	External power: 110V/220V power adapter (5 VDC)
Enclosure	Case material: 304 SS
	Wetted parts: 316 SS <sup>[3]</sup>
	Size: 4.65" x 1.77" x 6.89"(118mm x 42mm x 175mm)
	Weight: 1.58 lb (0.715 kg)
	Protection Level: IP67
Electrical Measurement Accuracy (23 ± 15°C)	Voltage DC: ±30.0000 V, ± (0.01%RD + 1.5 mV)
	Current DC: ±30.0000 mA, ± (0.01%RD + 1.5 µA)
	DC 24 V: 24 V ± 1 V, MAX: 30 mA
	Switch <sup>[4]</sup> : status OPEN/CLOSED, support for mechanical switches and NPN/PNP digital switches
Data Logging	Data storage: 8GB (100M+ records)
	Mode: manual and automatic Interval-record: user selectable from 0.1 to 9999.9 second intervals
Compliance	Protection Level: IP67
	Vibration: 5 g (10-500 Hz) Shock Resistance: 8 g/11 ms CE
Communication	USB Type-C and Bluetooth included, RS232 or Wi-Fi (optional)
Warranty	1 year

[1] FS = -14.5 psi

[2] Applicable to ADT673-RD-CPX

[3] Wetted parts material types may vary by pressure range

Please refer to manual or contact to Additel for more information

[4] Trigger voltage 2.7V

[5] Available units are dependent on the overall pressure range

## PRESSURE RANGE

Metrology Made Simple

Gauge Pressure <sup>[1]</sup>						
P/N	Pressure Range		Media <sup>[2]</sup>	Accuracy		Burst Pressure
	(psi)	(bar)		%FS	%RD	
V15	-15	-1.0	G, L <sup>[3]</sup>	0.01(0.02, 0.05)	N/A	3x <sup>[4]</sup>
GP2	2	0.16	G, L	0.05	N/A	3x
GP5	5	0.35	G, L	0.01(0.05)	0.1	3x
GP10	10	0.7	G, L <sup>[3]</sup>	0.01(0.02, 0.05)	0.1	3x <sup>[4]</sup>
GP15	15	1.0	G, L <sup>[3]</sup>	0.01(0.02, 0.05)	0.1	3x <sup>[4]</sup>
GP30	30	2.0	G, L <sup>[3]</sup>	0.01(0.02, 0.05)	0.1	3x <sup>[4]</sup>
GP50	50	3.5	G, L	0.01(0.02, 0.05)	0.1	3x <sup>[4]</sup>
GP100	100	7.0	G, L	0.01(0.02, 0.05)	0.1	3x <sup>[4]</sup>
GP150	150	10	G, L	0.01(0.02, 0.05)	0.1	3x <sup>[4]</sup>
GP300	300	20	G, L	0.01(0.02, 0.05)	0.1	3x <sup>[4]</sup>
GP500	500	35	G, L	0.01(0.02, 0.05)	0.1	3x <sup>[4]</sup>
GP600	600	40	G, L	0.01(0.02, 0.05)	0.1	3x <sup>[4]</sup>
GP1K	1,000	70	G, L	0.01(0.02, 0.05)	0.1	3x <sup>[4]</sup>
GP1.5K	1,500	100	G, L	0.01(0.02, 0.05)	0.1	3x <sup>[4]</sup>
GP2K	2,000	140	G, L	0.01(0.02, 0.05)	0.1	3x <sup>[4]</sup>
GP3K	3,000	200	G, L	0.01(0.02, 0.05)	0.1	3x <sup>[4]</sup>
GP5K	5,000	350	G, L	0.01(0.02, 0.05)	0.1	3x <sup>[4]</sup>
GP10K	10,000	700	G, L	0.01(0.02, 0.05)	0.1	1.5x <sup>[5]</sup>
GP15K	15,000	1,000	G, L	0.05 (0.1)	0.1	1.5x
GP20K	20,000	1,400	G, L	0.05 (0.1)	N/A	1.5x
GP25K	25,000	1,600	G, L	0.05 (0.1)	N/A	1.5x
GP30K	30,000	2,000	G, L	0.05 (0.1)	N/A	1.5x
GP36K	36,000	2,500	G, L	0.05 (0.1)	N/A	1.5x
GP40K	40,000	2,800	G, L	0.05 (0.1)	N/A	1.35x
GP50K	50,000	3,500	G, L	0.1 (0.2)	N/A	1.2x
GP60K	60,000	4,200	G, L	0.1 (0.2)	N/A	1.1x

[1] Sealed gauge pressure for above 1,000 psi

[2] G=Gas, L=Liquid

[3] 0.02% FS for gas media only

[1] FS specification applies to the span of the range

## PRESSURE RANGE

Compound Pressure					
P/N	Pressure Range		Media	Accuracy (%FS)	Burst Pressure
	psig	bar.g			
CP2	±2	±0.16	G	0.05	3x
CP5	±5	±0.35	G, L	0.01	2x
			G	0.02	3x
CP10	±10	±0.7	G, L	0.01	2x
			G	0.02	3x
CP15	±15	±1.0	G, L	0.01	2x
			G	0.02	3x
CP30	-15 to 30	-1 to 2.0	G, L	0.01	2x
			G	0.02	3x
CP50	-15 to 50	-1 to 3.5	G, L	0.01	2x
			G	0.02	3x
CP100	-15 to 100	-1 to 7.0	G, L	0.01	2x
			G	0.02	3x
CP300	-15 to 300	-1 to 20	G, L	0.01	2x
			G	0.02	3x
CP500	-15 to 500	-1 to 35	G, L	0.01	2x
			G	0.02	3x
CP600	-15 to 600	-1 to 40	G, L	0.01	2x
			G	0.02	3x
CP1K	-15 to 1,000	-1 to 70	G, L	0.01	2x
			G	0.02	3x
CP2K	-15 to 2,000	-1 to 140	G, L	0.01	2x
			G	0.02	3x
CP3K	-15 to 3,000	-1 to 200	G, L	0.01	2x
			G	0.02	3x
CP5K	-15 to 5,000	-1 to 350	G, L	0.01	2x
			G	0.02	3x
CP10K	-15 to 10,000	-1 to 700	G, L	0.01	2x
			G	0.02	2x

Differential Pressure						
P/N	Pressure Range		Media	Accuracy (%FS) <sup>[1]</sup>	Burst Pressure	Static Pressure Range
	(inH <sub>2</sub> O)	(mbar)				
DP1	±1	±2.5	G	0.05 <sup>[2]</sup>	100x	±10 psi
DP2	±2	±5.0	G	0.05 <sup>[2]</sup>	100x	±10 psi
DP5	±5	±10	G	0.05 <sup>[2]</sup>	50x	±10 psi
DP10	±10	±25	G	0.05 <sup>[2]</sup>	20x	±10 psi
DP20	±20	±50	G	0.05	20x	±10 psi
DP30	±30	±75	G	0.05	20x	±10 psi
DP50	±50	±125	G	0.05	3x	±10 psi
DP100	±100	±250	G	0.02	3x	±15 psi
DP150	±150	±350	G	0.02	3x	50 psi
DP300	±300	±700	G	0.02	3x	50 psi

[1] FS specification applies to the span of the range. Accuracy includes one year stability.

[2] 0.05%FS accuracy (incl 6 months stability). One year accuracy is 0.05%FS calibration accuracy combined with 0.05%FS one year stability.

Barometric Pressure					
P/N	Pressure Range		Media	Accuracy	Burst Pressure
	Low	High			
BP	60 kPa	110 kPa	G	55 Pa	3x

Communication Types Supported				
Comm \ Model	ADT685	ADT685Ex	ADT686	ADT673
RS232	○	○	○	○
RS485	○			
WiFi			○	○
USB	●	●	●	●
Bluetooth(BLE)	●	●	●	●

● Included ○ Optional

Additel Software Compatibility Matrix								
Comm \ Model	ADT685/ADT685Ex				ADT686/ADT673			
	ACal	LogII	Land	Link	ACal	LogII	Land	Link
RS232	●	●	●		●	●	●	
RS485 only for ADT685	● <sup>[2]</sup>	● <sup>[2]</sup>	● <sup>[2]</sup>					
WiFi					●	●	●	● <sup>[1]</sup>
USB	●	●	●		●	●	●	
Bluetooth(BLE)				●				●

● Supported ○ Non Ex models only

[1] This configuration requires that the device be connected to ACloud via Wi-Fi to utilize the Additel Link app.

[2] 4-20mA output and RS-485 not available in ADT685Ex models.

# ADT673


## Advanced Digital Pressure Calibrators



Metrology Made Simple

### ORDERING INFORMATION

#### Model Number



#### Accessories Included

Rubber boot
Test leads (1) set
Rechargeable Lion battery (1 pc)
USB cable (type-C)
Power adapter
Silicone tube - 1 meter each (2 pcs for DP models only)
ISO 17025 accredited calibration certificate

#### Optional Accessories

Model number	Description
9903	Carrying case for (1) digital pressure gauge
9040	Hanging strap with magnet
9502	Additel/Log II real time data logging and graphical software
9530-BASIC	Additel/Acal Automated calibration software with asset management, basic version
9530-NET	Additel/Acal Automated calibration software with asset management, network version, Includes server installation and 1 user license
9050-EXT	RS 232 (DB9/M) extension cable, 9 feet
1220610724	Screen protector kit

Note: For oil-free applications contact Additel.